

PRESSURE & TEMPERATURE CHART RECORDER

Part No: PROPTCR/100C/SSCASE-463x335

- Case Dimension: 463x335mm - Temperature Range: 0~100°C

| Pressure Range | Order No |
|----------------|---------------------------|
| 10,000 PSI | PROPTCR/MODULAR-10,000PSI |
| 5,000 PSI | PROPTCR/MODULAR-5,000PSI |
| 3,000 PSI | PROPTCR/MODULAR-3,000PSI |
| 1,500 PSI | PROPTCR/MODULAR-1,500PSI |
| 1,000 PSI | PROPTCR/MODULAR-1,000PSI |
| 600 PSI | PROPTCR/MODULAR-600PSI |
| 300 PSI | PROPTCR/MODULAR-300PSI |



SPECIFICATION

Case

High quality heavy duty stainless steel AISI-316L; IP-65
Very suitable for offshore applications and industrial
fumes and for usage in the tropics
Absolutely watertight and dustproof
The case has a lockable front-hinged door, rugged
construction and designed to last

Chart Drive

Battery operated clock, multispeed off-60 min-96 min-12hr-1d Chart Size: 12"(300mm)

Socket

Screwed to case, stainless steel AISI-316L to NACE 9/16x18 UNF Female

Measuring Element

Bourdon tube, stainless steel AISI-316L to NACE modular system

Mountings

Portable

Window

Instrument glass, makrolon

Accuracy

±1% full scale

Charts

All units will be supplied with 100 chart Paper of Extra charts available at cost

Pens

Recording is done with disposable feltpen, hassle free and easy to replace Each recorder is supplied with a spare pen

Prosdata Engineering Sdn. Bhd. (549299-U)

GST NO: 001096613888

12A, Jalan Sungai Jeluh 32/192, Seksen 32, Kawasan Perindustrian Kemuning, 40460, Shah Alam, Selangor, Malaysia (GPS Coordinate : 2.991204,101.517609)

TEL: +603-5525 8311 E-mail: info@prosdata.com.my FAX: +603-5525 8411

Website: www.prosdata.com.my

